

Data sheet

Climatic Chamber KK 700 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download




Smart PRO - preview screen

TECHNICAL DATA

| | |
|----------------------|----------------------------|
| air convection | forced |
| chamber capacity [l] | 600 |
| working capacity [l] | 485 |
| controller | microprocessor PID |
| display | 7 full colour touch screen |

TEMPERATURE AND HUMIDITY


| | |
|--|---------------------------------|
| temperature range [°C] | 0...+60 |
| temperature resolution every ... [°C] | 0,1 |
| temperature variation at 25°C and 60%rH [±°C]* | 2,0 |
| relative humidity range [%] | 30...90 (see chart for details) |
| humidity resolution every ... [%] | 1,0 |
| humidity variation at 25°C and 60% rH [%rH] | 5,0 |
| over temperature protection | class 3.3 to DIN 12880 |



CHAMBER

| | |
|-----------------|---|
| door type | double (external solid, internal glass) / external glass (option) |
| interior | |
| Smart PRO | DIN 1.4301 |
| IG Smart PRO | DIN 1.4301 |
| housing | |
| Smart PRO | powder coated sheet |
| IG Smart PRO | stainless steel linen finish |

| overall dims [mm] /1/ | |
|-----------------------|------|
| width A | 750 |
| height B | 1990 |
| depth C | 1070 |
| internal dims [mm] | |
| width D | 530 |
| width D' | 600 |
| height E | 1510 |
| depth F | 650 |
| height I | 1350 |



| | |
|--|--------|
| shelves (standard max) | 3 11 |
| max shelf workload [kg] /2/ | 30 |
| - reinforced shelf version (PW) [kg] /3/ | 100 |
| max unit workload [kg] | 150 |
| weight [kg] | 170 |


ELECTRICAL PARAMETERS

| | |
|-------------------|-------------------|
| voltage** | 230V 50-60Hz |
| nominal power [W] | 1850 |
| refrigerant | R290 / GWP=3 |
| warranty | 24 months |
| manufacturer | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)
 * - variation (K) calculated for chamber as: $K = \pm (T \text{ average max.} - T \text{ average min.}) / 2$
 ** - other power supplies on request
 1 - depth doesn't include 50 mm of power cable
 2 - on uniformly loaded surface
 3 - reinforced shelf
 4 - reinforced version

all the above technical data refer to standard units (without optional accessories)
 * - variation (K) calculated for chamber as: $K = \pm (T \text{ average max.} - T \text{ average min.}) / 2$
 ** - other power supplies on request
 1 - depth doesn't include 50 mm of power cable
 2 - on uniformly loaded surface
 3 - reinforced shelf
 4 - reinforced version

OPTIONS AND ACCESSORIES




Order number: */A

door with viewing window



Order number: */P INOX

Stainless steel wire shelf INOX




Order number: */PP

Perforated shelf



Order number: */PW

Reinforced shelf




Order number: KUW GN*/*

Stainless steel cuvettes



Order number: */FIT

Phytotron system




Order number: FIT/R3

FIT panels independent control



Order number: GNZ

Internal socket



Order number: KK/CP

Low water level sensor



Order number: BRT*/L or IQ/OQ/PQ

Calibration and IQ, OQ, PQ qualification



Order number: BPP 12

Battery backup for display




Order number: PORT ALARM

Dry alarm contact




Order number: USBK

USB cable




Order number: LANK

LAN cable




Order number: OCZ/20

Non-standard access port 20 mm




Order number: OCZ/30

Additional access port 30 mm




Order number: OCZ/60

Non-standard access port 60 mm



Order number: OCZ/100

Non-standard access port 100 mm



Order number: KK/Z

Container for deionised water


ALEPH

Part Science · Part Art



Order number: KD

Access control



Order number: CCTV

Camera inside the chamber



Order number: CCTV CAM

Additional camera