

## Data sheet

## Climatic Chamber KKS 115 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

### Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download




Smart PRO - preview screen

## TECHNICAL DATA

air convection	forced
chamber capacity [l]	109
working capacity [l]	109
controller	microprocessor PID
display	7 full colour touch screen

## TEMPERATURE AND HUMIDITY


temperature range [°C]	0...+100
temperature resolution every ... [°C]	0,1
temperature variation at 25°C and 60%rH [±°C]*	2,0
relative humidity range [%]	10...90 (see chart for details)
humidity resolution every ... [%]	1,0
humidity variation at 25°C and 60% rH [%rH]	5,0
over temperature protection	class 3.3 to DIN 12880



## CHAMBER

door type	double (external solid, internal glass) / external glass (option)
<b>interior</b>	
Smart PRO	DIN 1.4301
IG Smart PRO	DIN 1.4301
<b>housing</b>	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish

overall dims [mm] /1/	
width A	670
height B	1340
depth C	820
internal dims [mm]	
width D	460
height E	530
depth F	440



shelves (standard   max)	2   7
max shelf workload [kg] /2/	10
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	60
weight [kg]	122

## ELECTRICAL PARAMETERS

voltage**	230V 50-60Hz
nominal power [W]	2900
refrigerant	R1234ze / GWP=1
warranty	24 months
manufacturer	POL-EKO-APARATURA

txt_opis pod tabelą	<p>all the above technical data refer to standard units (without optional accessories) and without a reverse osmosis system</p> <p>* - variation (K) calculated for chamber as: <math>K = \frac{+/- (T \text{ average max.} - T \text{ average min.})}{2}</math></p> <p>** - other power supplies on request</p> <p>1 - depth doesn't include 50 mm of power cable</p> <p>2 - on uniformly loaded surface</p> <p>3 - reinforced shelf</p> <p>4 - reinforced version</p>
---------------------	---

all the above technical data refer to standard units (without optional accessories) and without a reverse osmosis system

\* - variation (K) calculated for chamber as:  $K = \frac{+/- (T \text{ average max.} - T \text{ average min.})}{2}$

\*\* - other power supplies on request

1 - depth doesn't include 50 mm of power cable

2 - on uniformly loaded surface

3 - reinforced shelf









4 - reinforced version

## OPTIONS AND ACCESSORIES



Order number: \*/A

door with viewing window

	Order number: */P INOX	Stainless steel wire shelf INOX
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
	Order number: KUW GN*/*	Stainless steel cuvettes
	Order number: GNZ	Internal socket
	Order number: BRT*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
	Order number: BPP 12	Battery backup for display
	Order number: PORT ALARM	Dry alarm contact
	Order number: USBK	USB cable
	Order number: LANK	LAN cable
	Order number: OCZ/20	Non-standard access port 20 mm
	Order number: OCZ/30	Additional access port 30 mm
	Order number: OCZ/60	Non-standard access port 60 mm
	Order number: OCZ/100	Non-standard access port 100 mm
	Order number: KD	Access control
	Order number: CCTV	Camera inside the chamber
	Order number: CCTV CAM	Additional camera