

Data sheet

Drying Oven with nitrogen blow SLWN 115 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs $% \left(\mathbf{r}_{1}\right) =\mathbf{r}_{1}$
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download




Smart PRO - preview screen



TECHNICAL DATA		
air convection	forced	
chamber capacity [I]	112	
working capacity [I]	112	
controller	microprocessor PID	
display	7 full colour touch screen	
TEMPERATURE		
temperature range [°C]	5°C above ambient temperature +300°C	
temperature resolution every [°C]	0,1	
temperature fluctuation at 105°C [+/-°C]*	0,2	
temperature variation at 105°C [+/-°C]*	2,0	
over temperature protection	class 3.1 to DIN 12880	
CHAMBER		
door type	solid / door with viewing window (option)	
interior		
Smart PRO	DIN 1.4301	
IG Smart PRO	DIN 1.4301	
housing		
Smart PRO	powder coated sheet	
IG Smart PRO	stainless steel linen finish	

overall dims [mm] /1/	
width A	660
height B	850
depth C	710
internal dims [mm]	
width D	460
height E	540
depth F	450



shelves (standard max)	2 7
max shelf workload [kg] /2/	25
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	60
- reinforced unit version (W) [kg] /4/	120
weight [kg]	65



voltage**	230V 50-60Hz
nominal power [W]	2500
warranty	24 months
manufacturer	POL-EKO-APARATURA
	Available models: SLWN1 the kit includes connections, valves and a laboratory rotameter (which can be calibrated) SLWN2 the kit includes connections, valves and a tech rotameter (which cannot be calibrated) type of rotameter must be specified while placing an order (it is not possible to change a technical rotameter into a laboratory one and vice versa)
txt_opis pod tabelą	all the above technical data refer to standard units (without optional accessories) * - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K= +/- (T average max T average min.) / 2 ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable 2 - on uniformly loaded surface 3 - reinforced shelf 4 - reinforced version

Available models:

SLWN1 the kit includes connections, valves and a laboratory rotameter (which can be calibrated)

SLWN2 the kit includes connections, valves and a tech rotameter (which cannot be calibrated)

type of rotameter must be specified while placing an order (it is not possible to change a technical rotameter into a laboratory one and vice versa)

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K = +/- (T average max. - T average min.) / 2

- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 reinforced version

OPTIONS AND ACCESSORIES

	Order number: */A	door with viewing window
INOX	Order number: */P INOX	Stainless steel wire shelf INOX
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
	Order number: KUW GN*/*	Stainless steel cuvettes
Ø	Order number: QLK*	Wheels



	Order number: */S or */S INOX	Table with wheels
	Order number: */ST or */S INOX	Base on castors
KG	Order number: */W	Reinforced version
	Order number: OWW/OWW LED	Interior lighting
	Order number: PT 100	Additional temperature sensor
НЕРА	Order number: HEPA	HEPA Clean Air Filter
>0<	Order number: BRT/*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
+	Order number: BPP 12	Battery backup for display
ALARM	Order number: PORT ALARM	Dry alarm contact
USB	Order number: USBK	USB cable
LAN	Order number: LANK	LAN cable
(((•)))	Order number: KD	Access control